



	A	A <sub>max</sub>	B	C	D	E	F	G	H	I	J
600.4	6950	14171	5023	4220	2300	1500	2600	1994	2798	4187	2450
600.5	7000	16310	5023	4250	2269	1500	2676	2010	2798	4277	2510
600.6	7075	18450	5023	4280	2229	1500	2691	2066	2798	4367	2550
600.7	7154	20371	5023	4308	2203	1500	2716	2083	2798	4457	2550

600.4	m	2.03	2.5	4.26	5.96	7.77	9.65	11.57			
	kg	30000	24550	14692	10488	8030	6480	5299			
600.5	m	2.02	2.5	4.33	6.03	7.84	9.72	11.64	13.66		
	kg	30000	24320	14224	10147	7748	6224	5067	4205		
600.6	m	2	2.5	4.37	6.07	7.88	9.77	11.69	13.71	15.77	
	kg	30000	24100	13874	9870	7509	5992	4855	4010	3306	
600.7	m	1.99	2.5	4.4	6.1	7.9	9.95	11.8	13.9	15.9	17.9
	kg	30000	23900	13580	9631	7310	5704	4640	3795	3129	2612

This load chart is based on 2 conditions:

- I. Outrigger fully extended
- II. Mounted on testing base

## Technical Data

	Lifting capacity (kN·m)	Outrigger Extension(m)	Rotation	Working pressure(MPa)	Pump capacity(cc/r)	Oil tank capacity(L)	Crane weight(kg)
600.4							6110±50
600.5							6344±50
600.6	600	5.8	∞	33	40-80	200	6574±50
600.7							6767±50

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.