



| | A | A _{max} | B | C | D | E | F | G | H | I | J |
|-------|------|------------------|------|------|------|------|------|------|------|------|------|
| 230.2 | 6680 | 10316 | 4600 | 4062 | 2412 | 1500 | 2411 | 1916 | 2460 | 4000 | 2280 |
| 230.3 | 6756 | 12419 | 4680 | 4093 | 2301 | 1500 | 2500 | 1936 | 2540 | 4100 | 2380 |
| 230.4 | 6852 | 14257 | 4743 | 4106 | 2190 | 1500 | 2597 | 1961 | 2600 | 4200 | 2450 |
| 230.5 | 6948 | 16095 | 4743 | 4118 | 2079 | 1500 | 2690 | 1986 | 2600 | 4350 | 2500 |

Technical Data

| | Lifting capacity (KN.m) | Outrigger Extension(m) | Rotation | Working pressure(MPa) | Pump capacity(cc/r) | Oil tank capacity(L) | Crane weight(kg) |
|-------|-------------------------|------------------------|----------|-----------------------|---------------------|----------------------|------------------|
| 230.2 | 230 | 3.54 | 385° | 28.5 | 40~80 | 160 | 2950±50 |
| 230.3 | | | | | | | 3140±50 |
| 230.4 | | | | | | | 3380±50 |
| 230.5 | | | | | | | 3590±50 |

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

| | | | | | | | | | |
|-------|----|-------|------|------|------|------|------|------|------|
| 230.2 | m | 2.15 | 2.5 | 4.26 | 6.08 | 7.82 | | | |
| | Kg | 11000 | 9480 | 5587 | 3816 | 2877 | | | |
| 230.3 | m | 2.11 | 2.5 | 4.26 | 6.08 | 7.95 | 9.81 | | |
| | Kg | 11000 | 9280 | 5446 | 3701 | 2704 | 2171 | | |
| 230.4 | m | 2.07 | 2.5 | 4.29 | 6.11 | 7.98 | 9.9 | 11.8 | |
| | Kg | 11000 | 9108 | 5315 | 3568 | 2644 | 2091 | 1737 | |
| 230.5 | m | 2.04 | 2.5 | 4.29 | 6.1 | 7.98 | 9.9 | 11.8 | 13.8 |
| | Kg | 11000 | 8960 | 5221 | 3273 | 2444 | 1919 | 1609 | 1304 |

This load chart is based on 2 conditions:

- I. Outrigger fully extended
- II. Mounted on testing base